# MATERIAL SAFETY DATA SHEET ATD-8405, Glass bead

## **Material Safety Data Sheet**

Copyright, 2010, ATD TOOLS,INC. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing the ATD-8405 is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from ATD TOOLS,INC, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: ATD-8405, Glass bead. MANUFACTURER: ATD TOOLS, INC.

**DIVISION: Abrasives Systems Division** 

ADDRESS: 160 Enterprise Drive

Wentzville, MO,63385

Issue Date: 03/04/10 Supercedes Date: 03/04/10 Document Group: 05-01162

**Product Use:** 

Intended Use: Abrasive Product

#### **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	C.A.S. No.	% by Wt
Aluminum Oxide Mineral	1302-74-5	0.5-2.3
Quartz Silica	14464-46-1	72-73
Calcium oxide	1305-78-8	6.5-8
Magnesium oxide	1309-48-4	3.0-4.2
Sodium oxide	1313-59-3	
Potassium superoxide	12030-88-5	>14.5-15.5

## **SECTION 3: HAZARDS IDENTIFICATION**

# 3.1 EMERGENCY OVERVIEW

Odor, Color, Grade: Solid Abrasive Product

General Physical Form: Solid

**Immediate health, physical, and environmental hazards:** This document covers only for the ATD-8405. For complete assessment, when determining the degree of hazard, the material being

abraded must also be considered.

## **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Dust created by cutting, grinding, sanding, or machining may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Skin Contact:**

Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

#### Inhalation:

Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

## Ingestion:

attention.

Ingest the glass bead :signs/symptoms may include itching, cough and throat pain.

## **SECTION 4: FIRST AID MEASURES**

#### **4.1 FIRST AID PROCEDURES**

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. **Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Spit out it. If signs/symptoms persist, get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

#### **5.1 FLAMMABLE PROPERTIES**

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

## **5.2 EXTINGUISHING MEDIA**

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

#### **5.3 PROTECTION OF FIRE FIGHTERS**

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable. None inherent in this product.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **Accidental Release Measures:**

Not applicable.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1 HANDLING

For industrial or professional use only. Avoid breathing of dust created by sanding, grinding or machining. Avoid eye contact with dust or airborne particles. Damaged product can break apart during use and cause serious injury to face or eyes. Check product for damage such as cracks or nicks prior to use. Replace if damaged. Always wear eye and face protection when working at sanding or grinding operations or when near such operations. Sparks and particles flying from the product during sanding or grinding can cause injury and fire.

#### 7.2 STORAGE

Store in a cool, dry place.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### **8.1 ENGINEERING CONTROLS**

Provide ventilation adequate to control dust concentrations and/or control dust. Provide appropriate local exhaust ventilation for sanding, grinding or machining. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures and/or control dust, fume, or airborne particles. If ventilation is not adequate, use respiratory protection equipment.

## **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

# 8.2.1 Eye/Face Protection

Avoid eye contact. To minimize the risk of injury to face and eyes, always wear eye and face protection when working at sanding or grinding operations or when near such operations.

The following eye protection(s) are recommended: Safety Glasses with side shields.

#### 8.2.2 Skin Protection

Avoid skin contact. Wear appropriate gloves to minimize risk of injury to skin from contact with dust or physical abrasion from grinding or sanding.

#### 8.2.3 Respiratory Protection

Avoid breathing of dust created by sanding, grinding or machining. Assess exposure concentrations of all materials involved in the work process. Consider material being abraded when determining the appropriate respiratory protection. Select and use appropriate respirators to prevent inhalation overexposure.

#### 8.2.4 Prevention of Swallowing

Not an expected route of exposure. Wash hands after handling and before eating.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Odor, Color, Grade: Solid Abrasive Prod

General Physical Form: Solid

Autoignition temperature Not Applicable Flash Point Not Applicable Flammable Limits - LEL Not Applicable Flammable Limits - UEL Not Applicable **Boiling point** Not Applicable **Vapor Density** Not Applicable **Vapor Pressure** Not Applicable **Specific Gravity** Not Applicable рΗ Not Applicable **Melting point** Not Applicable Solubility in Water Not Applicable **Evaporation rate** Not Applicable Kow - Oct/Water partition coef Not Applicable **Viscosity** Not Applicable

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

**Materials and Conditions to Avoid:** 

10.1 Conditions to avoid

None known

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# SECTION 12: ECOLOGICAL INFORMATION ECOTOXICOLOGICAL INFORMATION

Not determined.

## **CHEMICAL FATE INFORMATION**

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** The substrate that was abraded must be considered as a factor in the disposal method for this product.

Dispose of waste product in a sanitary landfill. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

# EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal

#### **SECTION 14:TRANSPORT INFORMATION**

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. ATD TOOLS,INC. does not guarantee the accuracy of this classification information. This information applies only to transportation classification and <u>not</u> the packaging, labeling, or marking requirements.

## **SECTION 15: OTHER INFORMATION**

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. ATD TOOLS,INC. MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of this product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate this product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

ATD TOOLS,INC. provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, ATD TOOLS,INC. makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from ATD TOOLS,INC.