

WARNING 🔺


WARNING: This product contains chemicals, including lead, known to the State of California to cause cancer, birth defects or other reproductive harm. Wash hands after handling.

> Made in Taiwan to ATD Tools, Inc. Specifications Visit us at www.atdtools.com


> > Revised January, 2017

ATD Tools, Inc. Wentzville, MO 63385


OPERATION:




1. Pull back the adjusting locking knob to unlock the handle.



2. Turn clockwise or counter-clockwise to set the desired torque.




3. Push back the adjusting locking knob to lock the handle.




CAUTION:

- While setting the desired torque, the arrow must line up with the scale before pushing back the adjustment locking knob, otherwise it may damage the inner mechanism.
- 2. Stop wrenching the torque wrench when you hear a "click" sound in order to prevent over-torquing the nuts/fasteners.
- 3. Never use your torque wrench to apply more torque than it's rated capacity. This will affect the calibration.



4. Apply a steady force to the center of handle, and stop wrenching when you hear a "click" sound.



| | Read, study, understand and follow all instructions before using. Always wear safety goggles (including bystanders). Do not use a "cheater bar". Do not use torque wrenches to loosen fasteners. Do not submerge this unit into any fluid. This product may contain one or more chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands thoroughly after handling. Failure to heed these warnings may result in personal injury and/or property damage. |
|--|--|

CERTIFICATION

This torque wrench was calibrated prior to shipment from the factory within tolerance limits of +/- 3% clockwise (right handed) accuracy of upper 80% of range.

LIMITED WARRANTY

Until one year from the date of purchase, we will repair any defect in material or workmanship free of charge. Improper use of these products, including but not limited to the application of excessive force, will affect performance and may result in injury. The warranty does not apply to wrenches which do not function properly or within specified accuracy because of wear, improper or unreasonable use, damage not resulting from defect or malfunction, or which have been altered. Calibration is warranted for 90 days. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. For repair or calibration send wrench, postage prepaid, to:

ANGLE REPAIR SERVICES, INC. 175 ANGLE DRIVE BECKLEY, WEST VIRGINIA 25801 304-253-5729