



RHO-17001 2-TON JACK STANDS OWNER'S MANUAL



Features:

- Welded foot pads provide added stability and resist sinking into soft ground of asphalt
- Counter-weighted pawl locks ratchet bar securely in place
- Sturdy, welded steel construction
- On-piece, multi-position ductile iron ratchet bar
- Meets or exceeds the current ASME PASE standards

Specifications:

- Model: RHO-17001
- Capacity Per Pair: 2 Tons
- Minimum Height: 10.38"
- Maximum Height: 16.19"
- Base Size: 7.13" x 6.25"

SAFETY AND WARNING INFORMATION



This is the safety notification symbol. This symbol will notify you of any potential injury hazards. Please follow all instructions that follow this symbol to avoid possible injuries or death.



Indicates a hazardous situation. If proper steps are not followed, death or serious injury could result.



IMPORTANT: Read All Instructions Before Use

Before using these jack stands, read this manual carefully. Understand the operating procedures, maintenance requirements, and all safety warnings.

If the operator is not fluent in English, the instructions must be read and explained in their native language to ensure comprehension.



Safety Guidelines:

- Study, understand, and follow all instructions.
- Use only as an identical pair.
- Maximum load capacity per identical pair shall not exceed the rated capacity of the individual stand.
- Use stands to support one end of a vehicle only.
- Use only on hard, level surfaces capable of supporting the load.
- Center load on the saddle.
- Locate saddles at vehicle manufacturer's designated support points.
- No alterations should be made to this product.
- Lift only at manufacturer-specified areas.
- Stands are not to be used to simultaneously support both ends of a vehicle.



Failure to follow instructions may result in injury or property damage.

INSPECTION

- This device shall be inspected immediately if the device is believed to have been subjected to abnormal load or shock. It is recommended that this inspection be made by a manufacturer's or supplier's authorized repair facility.
- Owners and/or operators should be aware that repair of this equipment may require specialized knowledge and facilities. It is recommended that an annual inspection of the product be made by a manufacturer's or supplier's authorized repair facility and that any defective parts, decals, or safety labels or signs be replaced with manufacturer's or supplier's specified parts.

DAMAGED EQUIPMENT AND ADD-ONS

- Any jack stand that appears to be damaged, is found to be worn or operates abnormally in any way must be **REMOVED FROM SERVICE AND DESTROYED IMMEDIATELY.**

Alterations

- Because of potential hazards associated with this type of equipment, no alterations shall be made to the product.

Attachments and Adapters

- Only attachments and/or adapters supplied by the manufacturer shall be used.

SETUP

- Prior to each use, visual inspection (as above) shall be made to the device by checking for abnormal conditions, such as cracked welds, damaged, loose or missing parts.
- Consult the vehicle owner's manual to determine the location of support points.
- Be sure to set the vehicle in park with the emergency brake on and wheels securely chocked.
- Be sure that the vehicle and the jack stands are on a hard, level surface.

ASSEMBLY

- Insert ratchet bar into collar.
- Lift ratchet bar upward to ensure the ratchet and locking pawl positively engage at each and every position.
- To lower, lift the handle, disengage the locking pawl from the ratchet bar and slowly move the ratchet bar down.
- Use a hammer and punch to bend the locking tab inward. This will prevent the ratchet bar from accidentally coming out of the base.

OPERATION AND MAINTENANCE

OPERATION

Supporting a Load

- Pull the ratchet bar up to desired position, ensure pawl and ratchet bar are securely engaged.
- Slowly lower the vehicle onto the stand. Be sure the load is centered on saddle.
- Ensure vehicle is secure and stable before working around or under vehicle.

Lowering Load

- Using a suitable jack, lift the vehicle clear of the jack stands.
- Disengage locking pawl from ratchet bar by raising the handle and adjust ratchet bar to lowest position.
- Remove stands. Follow procedures of jack operation to lower vehicle.


MAINTENANCE

Inspect each stand before use. Ensure all parts move freely. Only apply grease to the locking handle pivot point of this product and ensure all excess grease is wiped away before stand is used. If rust appears, sand away the rust area and cover with appropriate utility paint. Please note that there are no replacement parts available for this product.

ATTACHMENTS AND ADAPTERS

Only attachments and/or adapters supplied by the manufacturer shall be used. There are no attachments and/or adapters for this unit available by the manufacturer.

Typical Jack Stand Nomenclature:





THIS WARRANTY AND CONFIRMED RECEIPT(S) SHOULD BE RETAINED BY THE CUSTOMER AT ALL TIMES

PURCHASED FROM: _____

DATE PURCHASED: _____

INVOICE/RECEIPT NUMBER: _____

Your RHO-17001 is warranted for a period of 12 months from the original purchase date.

For a period of one (1) year from your purchase date, ATD Tools, Inc. will repair or replace (at its option) without charge, your ATD product if it was purchased new and the product has failed due to a defect in material or workmanship which you experienced during normal use of the product. This limited warranty is your exclusive remedy.

To access the benefits of this warranty, contact your supplier, or point of sale directly. You may be advised to return the product under warranty, freight prepaid, to your supplier for warranty determination.

If this ATD product is altered, abused, misused, modified, or undergoes service by an unauthorized technician, your warranty will be void. We are not responsible for damage to ornamental designs you place on this ATD product and such ornamentation should not cover any warnings or instructions or they may void the warranty. This warranty does not cover scratches, superficial dents, and other abrasions to the paint finish that occur under normal use. It also does not cover normal wear items such as but not limited to brushes, batteries, drill bits, drill chucks, pads or blades.

Subject to the law in your state:

- (1) Your sole and exclusive remedy is repair or replacement of the defective product as described above.
- (2) ATD is not liable for any incidental damages, including but not limited to, lost profits and unforeseeable consequences.
- (3) The repair and replacement of this product under the express limited warranty described above is your exclusive remedy and is provided in lieu of all other warranties, express or implied. All other warranties, including implied warranties and warranties of merchantability or fitness for a particular purpose are disclaimed and, if disclaimer is prohibited, these warranties are limited to one year from your date of purchase of this product.

Some states' laws do not allow limited durations on certain implied warranties and some states' laws do not allow limitations on incidental or consequential damages. You should consult the law in your state to determine how your rights may vary.

[Affix receipt or invoice here for safe keeping]