



PLACE
STAMP
HERE

PLATINUM
TECH™

TORQUE
WRENCHES



VISIT US ONLINE

TO VIEW THE FULL LINE OF ATD PRODUCTS AVAILABLE.

www.atdtools.com



Automotive Tools & Equipment for
the Professional Technician

PLATINUM
TECH™

REV. 11.5.21

BREAK BACK STYLE TORQUE WRENCHES

PLATINUM TECH

PLT-12600

3/4" Square Dr., 150-600 ft.-lbs.

- 200-800 Nm
- 3/4" Break Back
- Length: 49.21"
- Torque Accuracy: $\pm 4\%$

PLT-12750

1" Square Dr., 200-750 ft.-lbs.

- 300-1000 Nm
- 1" Break Back
- Length: 57.68"
- Torque Accuracy: $\pm 4\%$

FEATURES:

- Break back style wrenches provide a large break angle, to prevent the possibility of over-torquing
- Chrome molybdenum ratchet gear and fully heat-treated handle
- Ideal for noisy and difficult working conditions
- Comes in blow-molded storage case with instructions



MICROMETER TORQUE WRENCHES



FEATURES:

- Knurled handle for non-slip grip
- Easy-to-read stamped scale on beam and thimble collar
- Positive lock with spring-loaded pull-down lock ring
- Fast, accurate and easy to set
- Teardrop ratchet head
- 36-tooth gear
- Meets ISO 6789 specifications
- Calibrated on test equipment complying with ASME B107.300-2010 accuracy requirements
- Comes in blow molded storage case with instructions and calibration certificate
- Accuracy: $\pm 4\%$ CW from 20% to 100% of full scale

ATD-12500A

1/4" Dr., 40-200 in.-lbs.

ATD-12501A

3/8" Dr., 50-250 in.-lbs.

ATD-12502A

3/8" Dr., 20-100 ft.-lbs.

ATD-12504A

1/2" Dr., 50-250 ft.-lbs.

ATD-12505A

3/4" Dr., 120-600 ft.-lbs.



5-in-1 PRE-SET TORQUE WRENCH




FEATURES:

- Fast and easy to use
- Heat treated steel shaft
- Comfort grip handle
- Accurate to within $\pm 4\%$
- Meets ISO 6789, U.S. Fed. GGG-W-686 and ANSI Spec. B107.14M

ATD-12555

5 pre-set torque values:
80, 100, 120, 140 and
160 ft.-lbs.



USA MADE TORQUE WRENCHES



FEATURES:

- Knurled metal handle for non-slip grip
- Easy-to-read laser marked dual scales
- Positive lock with spring loaded pull down lock ring
- Fast, accurate and easy to set
- Quick release ratchet head for positive socket retention and easy removal
- Accuracy: $\pm 4\%$ CW $\pm 4\%$ CCW of indicated value, CW from 20% to 100% of full scale
- Certified to meet the accuracy in specifications: ASME B107.14-2004, GGG-W-686, Type 2, Class A Style 1, 2 and ISO 6789
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.
- Comes in a blow molded storage case with instructions and calibration certificate
- Made in USA with US and foreign parts

ATD-2505

3/4" Dr., 100-600 ft.-lbs.

ATD-2504

1/2" Dr., 30-250 ft.-lbs.

